

ENERGIZER L91-FR6


AA



Industry Standard Dimensions

(millimeters)

This battery has Underwriters Laboratories component recognition (MH29980)




Specifications

Classification:	Lithium
Chemical System:	Lithium/Iron Disulfide (Li/FeS ₂)
Designation:	IEC-FR6
Nominal Voltage:	1.5 Volts
Storage Temp:	-40°C to 60°C
Operating Temp:	-40°C to 60°C
Typical Weight:	14.5 grams
Typical Volume:	8.0 cubic centimeters
Max Discharge:	2.0 amps continuous 3.0 amps pulse (2 sec on/8 sec off)
Max Rev Current:	2 uA
Typical Li Content:	0.98 grams
Shelf Life:	15 years at 21°C (90% of rated capacity)
Shipping:	For complete details, please reference: Global (except US): Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations United States: 49 CFR 173.185

Milliamp-Hours Capacity

Constant Current Discharge to 0.9 Volts at 21°C




Milliwatt-Hours Capacity at Cold/Room Temperature

Constant Power Discharge to 1.0 Volts at 0°C and 21°C


Cold Temperature (0°C)

Constant Power Discharge



Room Temperature (21°C)

Constant Power Discharge



Important Notice

This datasheet contains typical information specific to products manufactured at the time of its publication.
©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.

ENERGIZER L91-FR6


AA

Typical Discharge Curve Characteristics

Constant Current Discharge at 21°C (low and high drains)


Low Drain Performance

50mA Continuous (21°C)




High Drain Performance

1000mA Continuous (21°C)




Constant Power Performance

Typical Characteristics to 1.0 Volts (21°C)



Constant Current Performance


Typical Characteristics to 1.0 Volts (21°C)



Industry Standard Tests (21°C)


REMOTE
24 ohm 15 sec/min 8 hrs/day

RADIO
43 ohm 4 hrs/day




CD/GAMES
250 mA 1 hr/day

TAPE PLAYER
100 mA 1 hr/day




PORTABLE LIGHTING
3.3 ohm LIF

TOY
3.9 ohm 1 hr/day



PHOTOFLASH
1K mA 10 sec/min 1 hr/day

DIGITAL CAMERA
1.5/.65K mW 2/.1/27.9s 10X



Important Notice

This datasheet contains typical information specific to products manufactured at the time of its publication.
©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.